



02M10701KWDE916 | silver

02M projector LED | 70 W 5700 K



- projector 02M
- for wall-, ground and ceiling mounting
- with mounting bracket, pivots in two axes
- with LED 11110 lm
- colour temperature: 5700 K
- colour rendering index: CRI 80
- L90 / B10 (50.000h) SDCM < 3
- net luminous flux: 7020 lm
- total load: 70 W
- luminous efficacy: 100,3 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 15 °
- with built in LED power unit, electronic (DALI),
- 220-240 V, 0/50/60 Hz - power supply: 5-pole supply cord 1 mm², Length: . 500 mm
- With circular connector RST16 (Wieland) for cables with diameter 7,1-13mm and cross section 0,25-2,5mm.
- Connection outside of the luminaire housing for easier installation
- housing of die cast aluminium
- safety glass, clear
- length: 293 mm, width: 271 mm, height: 326 mm
- pivotable -80°/+40°
- windage area: 0,06 m²
- weight: 5,9 kg protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- designed and manufactured in Germany
- maximum ambient temperature: 35 ° C
- impact resistance class: IK08
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver (RAL9006)
- 02M10701KWDE916
- Overview of accessories on the following page / s

02M10701KWDE916 accessory

Optional accessories

dimensions in mm	item number	picNo.
	814M05000916	01
	814M04000916	02
	802M0011721	03
	802M0012721	03
	802M0013721	03
	802M0014721	03
	802M0015721	03
	802M0016721	03
	dimensions in mm	814M05000916 814M04000916 802M0011721 802M0012721 802M0013721 802M0014721 802M0015721

