



02M5070WWDE916 | silver

02M projector LED | 70 W 3000 K

| LED | | | | |
|------|------|------|----|----|
| DALI | IP65 | ІКО8 | CE | 5Y |

- projector 02M
- for wall-, ground and ceiling mounting
- with mounting bracket, pivots in two axes
- with LED 10100 lm
- colour temperature: 3000 K
- colour rendering index: CRI 80
- L90 / B10 (50.000h) SDCM < 3
- net luminous flux: 6520 lm
- total load: 70 W
 luminous efficacy: 93,1 lm/W
- oval flood horizontal
- 15° x 40°
- with built in LED power unit, electronic (DALI), 220-240 V, 0/50/60 Hz
- power supply: 4-pole supply cord 1,5 mm², Length: . 500 mm
- With circular connector RST16 (Wieland) for cables with diameter 7,1-13mm and cross section 0,25-2,5mm.
- Connection outside of the luminaire housing for easier installation
- housing of die cast aluminium
- safety glass, clear
- length: 293 mm, width: 271 mm, height: 326 mm
 pivotable -80°/+40°
- windage area: 0,06 m²
- weight: 5,9 kg protection rating: IP65
- protection class II
- 5 years Hoffmeister warranty
- designed and manufactured in Germany
- maximum ambient temperature: 35 ° C
- impact resistance class: IK08
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver (RAL9006)
- 02M5070WWDE916
- Overview of accessories on the following page / s

02M5070WWDE916 accessory

Optional accessories

| dimensions in mm | item number | picNo. |
|------------------|------------------|---|
| | 814M05000916 | 01 |
| | 814M04000916 | 02 |
| | 802M0021721 | 03 |
| | 802M0022721 | 03 |
| | 802M0023721 | 03 |
| | 802M0024721 | 03 |
| | 802M0025721 | 03 |
| | 802M0026721 | 03 |
| | dimensions in mm | 814M05000916 814M04000916 802M0021721 802M0022721 802M0023721 802M0024721 802M0025721 |

