14L3250WWCE916 | silver

14L
projector
LED | 250 W 3000 K

LED

DMX | IP65 | III | IK08 | CE | 5Y





LED 3000 K 19890lm ⊲41°

h [m]	C0 Ø[m]	Em [lx]
1.0	0.74	26284
2.0	1.48	6571
3.0	2.22	2920
4.0	2.96	1643
5.0	3.70	1051

H0F17930

- projector 14L
- for wall-, ground and ceiling mounting
- power supply and mounting bracket must be ordered separately
- with LED 29850 lm
- colour temperature: 3000 K
- colour rendering index: CRI >70
- L80 / B10 (50.000h)
- SDCM < 3
- net luminous flux: 19890 lm
- total load: 250 W
- luminous efficacy: 79,6 lm/W
- flood
- beam angle: 40 °
- for external power supply, integrated control unit (DMX)
- 48V DC
- control ON/OFF, DMX
- secondary connection:
- with two connection cables length 500mm and circular connector 2-pole supply (type: RST16i5 for 48V (Wieland), RST16i3 for DMX (Wieland))
- housing of die cast aluminium
- safety glass, clear
- length: 328 mm, width: 429 mm, height: 464 mm
- windage area: 0,15 m²
- weight: 9,823 kg
- protection rating: IP65
- protection class III
- 5 years Hoffmeister warranty
- designed and manufactured in Germany
- impact resistance class: IK08
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver (RAL9006)
- 14L3250WWCE916

- Overview of accessories on the following page / s

Colour and technicial specification of the photos can differ from the product description.
All technical attributes are subject to change without prior notice. Any errors excepted.

14L3250WWCE916
accessory

Required accessories

description accessory general	dimensions in mm	item number	pic.-No.
LED power unit IP67, 48V / 320W for projector 14L for outdoor usage	LxWxH: 251 x 90 x 44	814L25000	01
Pivoting bracket for projector 14L		814L0010H916	02
Standard bracket for projector 14L		814L00100916	03

01

02

03

Optional accessories

description accessory general	dimensions in mm	item number	pic.-No.
Screen 45° for projector 14L		814L00545916	01

01

Colour and technicial specification of the photos can differ from the product description.
All technical attributes are subject to change without prior notice. Any errors excepted.