




177F965WW70D | black

177 | BLACK EDITION

Arealflooter

LED | 965 W 3000 K



- Arealflooter 177 BLACK EDITION
- for surface mounted installation on wall or ceiling
- mounting bracket must be ordered separately
- with LED 146900 lm
- colour temperature: 3000 K
- colour rendering index: CRI >70
- L90 / B10 (100.000 / ta 25°C)
- net luminous flux: 119000 lm
- total load: 965 W
- luminous efficacy: 123,3 lm/W
- symmetrical light distribution, very wide flood
- beam angle: 98 °
- electronic (DALI), 220-240 V, 0/50/60 Hz overvoltage protection 10kV; discharge current 5kA
- dimmable 10-100%
- Number of luminaires per fuse (B16): 1
- power supply: plug connector 5x2,5 mm²
- optional loop-in loop-out cabling
- housing of aluminium and die cast aluminium
- safety glass, clear
- length: 900 mm, width: 830 mm, height: 170 mm
- windage area: 0,75 m²
- weight: 43,6 kg
- protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- designed and manufactured in Germany
- minimum ambient temperature: -40 °C
- maximum ambient temperature: 40 °C
- impact resistance class: IK10
- certificates: manufactured according to DIN VDE 0711 / EN 60598
- colour: black
- 177F965WW70D

- Overview of accessories on the following page / s

177F965WW70D
accessory

Required accessories

description accessory general	dimensions in mm	item number	pic.-No.
Ceiling fixation for series 177		817700200	01
Mounting bracket, traverse mounting for series 177		817700300	02
Mounting bracket, for wall mounting		817700400	03

